



## Declaration of Performance (DoP)

<b>No. I18-CPR-130912</b>	
<b>Product Type:</b>	Insert appliance
<b>Type, batch or serial number:</b>	<b>Jøtul I 18 Panorama, Jøtul I 18 Harmony</b>
<b>Intended use of the product:</b>	Insert burning solid fuel without water supply
<b>Name and Address of the manufacturer:</b>	Jøtul AS Postboks 1411, 1602 Fredrikstad, Norway Tel.: +47 69 35 90 00 E-mail: post@jotul.no
<b>AVCP:</b> <i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i>	System 3
<b>Notified body:</b>	Rhein-Ruhr Feuerstätten Prüfstelle
NB-No:	1625
Test report no:	RRF - 29 03 497
<b>Declared performance:</b>	
Harmonized technical specification	EN 13229:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm Floor = 257 Front = 1000 Combustible materials inside the surround must be covered by insulation as described in the manual
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,09 %]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [278°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Normal heat output	10 kW
Room heating output	- kW
Water heating output	-*kW
Energy efficiency	$\eta$ [81%]

**Declaration:**

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager

---

*(Name and function)*

Fredrikstad, August 23rd 2013

---

*(Place and date of issue)*

Tom J. Berglind

---

*(Signature)*