

(EN) **DECLARATION OF PERFORMANCE**

according to Regulation (EU) 305/2011

No. H07900033-CPR-2013/07/01

- | | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. Unique identification code of the product type : | IL 65/54 , Inset appliance fired by solid fuels without hot water supply
EN13229:2001/A2:2004/AC:2007 |
| 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): | IL 65/54 |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | Inset appliance fired by solid fuels without hot water supply |
| 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5): | PIAZZETTA
Gruppo Piazzetta S.p.A.
Via Montello, 22 - 31011 Casella d'Asolo (TV) – Italy
Tel. +3904235271 Fax: +39042355178 email: info@gruppopiazzetta.com |
| 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): | - |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: | System 3 |
| 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: | The notified laboratory RRF PRÜFSTELLE No 1625 performed the determination of the product type on the basis of type testing under system 3 and issued test report RRF29112781 |

8. Declared performance

Essential Characteristics	Performance	Harmonized technical specification
Fire safety		
Reaction to fire	A1	EN13229:2001/A2:2004/AC:2007
Distance to combustible materials insulation thickness rear = insulation thickness sides = insulation thickness ceiling = front = insulation thickness floor =	Minimum distances, in cm 20 20 - 100 10	EN13229:2001/A2:2004/AC:2007
Risk of burning fuel falling out	Pass	EN13229:2001/A2:2004/AC:2007
Emission of combustion products		
at nominal heat output	CO [0,070 %] NOx [179,00 mg/Nm ³] THC [40,00 mg/Nm ³] PM [21,0 mg/Nm ³]	EN13229:2001/A2:2004/AC:2007
Surface Temperature	Pass	EN13229:2001/A2:2004/AC:2007
Electrical safety	NPD (no performance determined)	EN 60335-2-102: 2007/A1:2011
Cleanability	Pass	EN13229:2001/A2:2004/AC:2007
Maximum operating pressure	- bar	EN13229:2001/A2:2004/AC:2007
Flue gas temperature at nominal heat output	T [303,0 °C]	EN13229:2001/A2:2004/AC:2007
Mechanical resistance (to carry a chimney/flue)	NPD (no performance determined)	EN13229:2001/A2:2004/AC:2007
Thermal output		
Nominal heat output Room heating output Water heating outpur	7,5 kW - kW - kW	EN13229:2001/A2:2004/AC:2007
Energy efficiency		
at nominal heat ouput	η [78,1 %]	EN13229:2001/A2:2004/AC:2007

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by Carlo Piazzetta (Chief Executive Officer)

Casella d'Asolo , 2013/07/01


(signature)