

Appliances properties: HOXTER a.s. - HAKA 60/50 Th

Master data	
Date of entry	Oct 26, 2021
Manufacturer	HOXTER a.s.
Model	HAKA 60/50 Th
Nominal heat output [kW]	7
Continuous burning appliance	_
Type test standard	DIN EN 13229
Year of testing	2019
Test laboratory	Strojirensky Zkusebni Ustav s.p.
Number of test laboratory	19
Number of test report	30-14266/4/T

Flue gas values

	Wood
Flue gas mass flow [g/s]	7.2
Flue gas mass flow [g/s]	236
Necessary flue draught [Pa]	11

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	•
Connectivity to the central heating system	_
General technical approval for room sealed operation	_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood	
Norm : Inset appliances (with closed firedoor)	Evaluation
0 - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	×
- Crédit d'impôt à la transition énergétique	74

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	!
DK - Danish regulation for air pollution from wood burners	•