## Appliances properties: BRUNNER - HKD 2.2 XL-SK/h DHT

Master data		
Date of entry	Feb 19, 2015	
Manufacturer	BRUNNER	
Model	HKD 2.2 XL-SK/h DHT	1
Nominal heat output [kW]	13	-
Declared nominal space heating output [kW]	3	
Nominal water heating output [kW]	9.1	
Water operating pressure [bar]	3	
Continuous burning appliance	_	-1
Гуре test standard	DIN EN 13229	4
Year of testing	2014	1
Test laboratory	TÜV SÜD Industrie Service GmbH	
Number of test laboratory	1	
Number of test report	W-O 1414-00/14	

Flue gas values	
	Wood
Flue gas mass flow [g/s]	9.6
Flue gas mass flow [g/s]	154
Necessary flue draught [Pa]	14

Further important characteristics of the appliance

## Suitability for installation to a shared flue<sup>1)</sup> Connectivity to the central heating system General technical approval for room sealed operation

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	× .
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	<u> </u>

## Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	