Appliances properties: Supra S.A. - Schönbrunn - Marke Worldkamin

Master data	
Date of entry	Feb 26, 2008
Manufacturer	Supra S.A.
Model	Schönbrunn
Product code	Marke Worldkamin
Nominal heat output [kW]	10
Continuous burning appliance	—
Type test standard	DIN 18891
Year of testing	2001
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RO-91 01 348

Flue gas values

	Wood	
Flue gas mass flow [g/s]	9	
Flue gas mass flow [g/s]	318	
Necessary flue draught [Pa]	11	

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	_
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation Stufe 1 Grandfathering
D - 1.BImSchV	
A - Austrian regulation referred to Art 15a B-VG	
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	
F - Crédit d'impôt à la transition énergétique	×

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Grandfathering
A - Austrian regulation referred to Art 15a B-VG	-
CH - Swiss clean air act	×