

ſ

Appliances properties: Rüegg Cheminée Schweiz AG - Merkur 510/570 K flach

ManufacturerRüegg Cheminée Schweiz AGModelMerkur 510/570 K flachNominal heat output [kW]5Declared nominal space heating output [kW]5Continuous burning applianceImage: Continuous burning applianceType test standardDIN EN 13229Year of testing2012Test laboratoryRRF Rhein-Ruhr-Feuerstättenprüfstelle GmbHNumber of test laboratory2	Master data	
ModelMerkur 510/570 K flachNominal heat output [kW]5Declared nominal space heating output [kW]5Continuous burning applianceImage: Continuous burning applianceType test standardDIN EN 13229Year of testing2012Test laboratoryRRF Rhein-Ruhr-Feuerstättenprüfstelle GmbHNumber of test laboratory2	Date of entry	Sep 25, 2012
Nominal heat output [kW]5Declared nominal space heating output [kW]5Continuous burning appliance—Type test standardDIN EN 13229Year of testing2012Test laboratoryRRF Rhein-Ruhr-Feuerstättenprüfstelle GmbHNumber of test laboratory2	Manufacturer	Rüegg Cheminée Schweiz AG
Declared nominal space heating output [kW]5Continuous burning appliance—Type test standardDIN EN 13229Year of testing2012Test laboratoryRRF Rhein-Ruhr-Feuerstättenprüfstelle GmbHNumber of test laboratory2	Model	Merkur 510/570 K flach
Continuous burning appliance—Type test standardDIN EN 13229Year of testing2012Test laboratoryRRF Rhein-Ruhr-Feuerstättenprüfstelle GmbHNumber of test laboratory2	Nominal heat output [kW]	5
Type test standardDIN EN 13229Year of testing2012Test laboratoryRRF Rhein-Ruhr-Feuerstättenprüfstelle GmbHNumber of test laboratory2	Declared nominal space heating output [kW]	5
Year of testing2012Test laboratoryRRF Rhein-Ruhr-Feuerstättenprüfstelle GmbHNumber of test laboratory2	Continuous burning appliance	_
Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2	Type test standard	DIN EN 13229
Number of test laboratory 2	Year of testing	2012
· · · · · · · · · · · · · · · · · · ·	Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test report RRF - 29 00 48/RRF - 00 48	Number of test laboratory	2
	Number of test report	RRF - 29 00 48/RRF - 00 48

Flue gas values

Wood
4.8
288
14

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	_
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	× .
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	<u> </u>

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	