

Appliances properties: Oranier Heiztechnik GmbH - KE 706 Panorama - 7959 11

Master data		
Date of entry	Feb 25, 2011	
Manufacturer	Oranier Heiztechnik GmbH	
Model	KE 706 Panorama	
Product code	7959 11	
Nominal heat output [kW]	7	10000
Declared nominal space heating output [kW]	7	N. 15
Continuous burning appliance	- 1	
Type test standard	DIN EN 13240	
Year of testing	2004	
Test laboratory	RWE Rheinbraun AG	
Number of test laboratory	4.1	
Number of test report	FSPS-Wa 1318 EN	

Flue gas values

	Wood
Flue gas mass flow [g/s]	7
Flue gas mass flow [g/s]	330
Necessary flue draught [Pa]	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	-
General technical approval for room sealed operation	_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Stufe 2	orm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
L. Swiss clean air act	- 1.BImSchV	Stufe 2
	H - Swiss clean air act	× .

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation	
D - 1.BImSchV	Stufe 1 Grandfathering	
CH - Swiss clean air act	×	