

## Appliances properties: Rüegg Cheminée Schweiz AG - Terza

Master data		
ate of entry	Jul 26, 2010	
lanufacturer	Rüegg Cheminée Schweiz AG	
lodel	Terza	
ominal heat output [kW]	11	
eclared nominal space heating output [kW]	11	
ontinuous burning appliance	_	
ype test standard	DIN EN 13229	
ear of testing	2009	
est laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	_
umber of test laboratory	2	
umber of test report	RRF-29 09 2106	

Flue gas values

Wood
8
335
12

Further important characteristics of the appliance		
Suitability for installation to a shared flue <sup>1)</sup>	_	
Connectivity to the central heating system	-	
General technical approval for room sealed operation		

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Stufe 2
× .
×

## Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024