Appliances properties: Austroflamm GmbH - Flok 2.0 - O56006

Master data		
Date of entry	Jul 29, 2013	
Manufacturer	Austroflamm GmbH	
Model	Flok 2.0	
Product code	O56006	
Nominal heat output [kW]	4	
Declared nominal space heating output [kW]	4	
Partial load [kW]	2	
Part load space heating output [kW]	2	
Continuous burning appliance	-	
Thermal output	14,400	
Type test standard	DIN EN 13240	
Year of testing	2012	
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Number of test laboratory	2	
Number of test report	RRF - 40 12 3120	

Flue gas values	
	Wood
Flue gas mass flow [g/s]	3.92
Flue gas mass flow [g/s]	343
Necessary flue draught [Pa]	12

Suitability for installation to a shared flue¹⁾

Connectivity to the central heating system

General technical approval for room sealed operation

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	×
F - Crédit d'impôt à la transition énergétique	7☆

Evaluation of emission data and efficiency Lignite briquettes	
Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BlmSchV	!