Appliances properties: Austroflamm GmbH - Ke 71x57 S3 - 360029

Master data	
Date of entry	Jun 21, 2012
Manufacturer	Austroflamm GmbH
Model	Ke 71x57 S3
Product code	360029
Nominal heat output [kW]	10
Declared nominal space heating output [kW]	10
Partial load [kW]	3.4
Part load space heating output [kW]	3.4
Continuous burning appliance	-
Thermal output	36,000
Type test standard	DIN EN 13229
Year of testing	2010
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF - 29 10 2423

Flue gas values	
	Wood
Flue gas mass flow [g/s]	9.2
Flue gas mass flow [g/s]	330
Necessary flue draught [Pa]	12

Suitability for installation to a shared flue¹⁾

Connectivity to the central heating system

General technical approval for room sealed operation

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	✓
CH - Swiss clean air act	 ✓
F - Crédit d'impôt à la transition énergétique	7\$

Evaluation of emission data and efficiency Lignite briquettes	
Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	!