## Appliances properties: Camina & Schmid Feuerdesign und Technik GmbH & Co. KG - Lina 87 h/k

Master data		
Date of entry	Mar 6, 2012	
Manufacturer	Camina & Schmid Feuerdesign und Technik GmbH & Co. KG	
Model	Lina 87 h/k	6
Nominal heat output [kW]	10	
Continuous burning appliance	_	
Type test standard	DIN EN 13229	
Year of testing	2011	
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Number of test laboratory	2	
Number of test report	RRF - 29 10 2338	

## Flue gas values

Wood
8.9
230
12
-

Further important characteristics of the appliance	
Suitability for installation to a shared flue <sup>1)</sup>	
Connectivity to the central heating system	-
General technical approval for room sealed operation	-

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	× .
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	<u> </u>

## Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	