

Appliances properties: Spartherm Feuerungstechnik GmbH - Arte Bh (Bauart A ; ab 2008)

Master data	
Date of entry	Dec 6, 1970
Manufacturer	Spartherm Feuerungstechnik GmbH
Model	Arte Bh (Bauart A ; ab 2008)
Nominal heat output [kW]	11
Declared nominal space heating output [kW]	11
Continuous burning appliance	-
Type test standard	DIN EN 13229
Year of testing	2008
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF - 29 07 1268

Flue gas values

	Wood
Flue gas mass flow [g/s]	10.7
Flue gas mass flow [g/s]	350
Necessary flue draught [Pa]	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	-
Connectivity to the central heating system	_
General technical approval for room sealed operation	_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

 Image: A second sec second second sec
Stufe 2
2015
× .

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024