Appliances properties: Austroflamm GmbH - Rikk

Master data	
Date of entry	Dec 19, 2018
Manufacturer	Austroflamm GmbH
Model	Rikk
Nominal heat output [kW]	10
Declared nominal space heating output [kW]	10
Continuous burning appliance	<u> </u>
Thermal output	36,000
Type test standard	DIN EN 13240
Year of testing	2017
Test laboratory	DBI-Gastechnisches Institut gGmbH Freiberg
Number of test laboratory	12
Number of test report	DBI F 16/10/0419

Flue gas values

	Wood
Flue gas mass flow [g/s]	8.1
Flue gas mass flow [g/s]	313
Necessary flue draught [Pa]	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	-
General technical approval for room sealed operation	×
Number of approval for room sealed operation	Z43.12-273
¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).	

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
) - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	×
F - Crédit d'impôt à la transition énergétique	_

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	!
DK - Danish regulation for air pollution from wood burners	!