## Appliances properties: Austroflamm GmbH - Minos

Master data	
Date of entry	Aug 7, 2014
Manufacturer	Austroflamm GmbH
Model	Minos
Nominal heat output [kW]	10
Declared nominal space heating output [kW]	10
Continuous burning appliance	—
Thermal output	36,000
Type test standard	DIN EN 13229
Year of testing	2007
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF - 29 07 1282

Flue gas values

	Wood	
Flue gas mass flow [g/s]	9.6	
Flue gas mass flow [g/s]	330	
Necessary flue draught [Pa]	12	

Further important characteristics of the appliance	
Suitability for installation to a shared flue <sup>1)</sup>	
Connectivity to the central heating system	-
General technical approval for room sealed operation	-

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood		
Norm : Inset appliances (with closed firedoor)	Evaluation	
D - 1.BImSchV	Grandfathering	
A - Austrian regulation referred to Art 15a B-VG	—	
CH - Swiss clean air act	-	
F - Crédit d'impôt à la transition énergétique	-	

## Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024