

Appliances properties: Erwin Koppe GmbH - Caron 5 Kachel

Jan 5, 2018
Erwin Koppe GmbH
Caron 5 Kachel
5
—
DIN EN 13240
2010
RWE Rheinbraun AG
4.1
FSPS-Wa 1945-EN

 Flue gas values
 Wood

 Flue gas mass flow [g/s]
 5

 Flue gas mass flow [g/s]
 280

 Necessary flue draught [Pa]
 12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	-
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	× .
DK - Danish regulation for air pollution from wood burners	×
F - Crédit d'impôt à la transition énergétique	v

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	×