

Appliances properties: Rüegg Cheminée Schweiz AG - Mars 510 K flach oder rund mit Nachschaltheizfläche

Master data	
Date of entry	Sep 25, 2012
Manufacturer	Rüegg Cheminée Schweiz AG
Model	Mars 510 K flach oder rund mit Nachschaltheizfläche
Nominal heat output [kW]	8
Declared nominal space heating output [kW]	8
Continuous burning appliance	_
Type test standard	DIN EN 13229
Year of testing	2012
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF - 29 00 107/RRF - 00 107

Flue gas values

	Wood
Flue gas mass flow [g/s]	6.7
Flue gas mass flow [g/s]	240
Necessary flue draught [Pa]	14

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	_
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	× .
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	<u> </u>

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	