

Appliances properties: Dovre N.V. - 350CB(3)

Master data		
Date of entry	Dec 27, 2011	
Manufacturer	Dovre N.V.	
Model	350CB(3)	
Nominal heat output [kW]	6	
Declared nominal space heating output [kW]	6	
Continuous burning appliance	-	
Type test standard	DIN EN 13240	
Year of testing	2008	100
Test laboratory	LABORATORY K.V.B.G A.R.G.B.	•
Number of test laboratory	17	
Number of test report	H0037	

Flue gas values

Wood	
6.6	
298	
12	

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	_
Connectivity to the central heating system	_
General technical approval for room sealed operation	—

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	-
CH - Swiss clean air act	×
F - Crédit d'impôt à la transition énergétique	.

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing

Evaluation

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024

I