

## Appliances properties: Dovre N.V. - 550GM

Master data		
Date of entry	Apr 2, 2015	
Manufacturer	Dovre N.V.	
Model	550GM	
Nominal heat output [kW]	8	
Declared nominal space heating output [kW]	8	
Continuous burning appliance	_	
Type test standard	DIN EN 13240	
Year of testing	2011	
Test laboratory	LABORATORY K.V.B.G A.R.G.B.	- 1
Number of test laboratory	17	
Number of test report	H0084	

## Flue gas values

	Wood
Flue gas mass flow [g/s]	9.2
Flue gas mass flow [g/s]	290
Necessary flue draught [Pa]	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue <sup>1)</sup>	-
Connectivity to the central heating system	-
General technical approval for room sealed operation	-

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	× .
CH - Swiss clean air act	×
F - Crédit d'impôt à la transition énergétique	

## Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	