Appliances properties: Camina & Schmid Feuerdesign und Technik GmbH & Co. KG - SH 8G / 8GB

Master data		
Date of entry	Feb 21, 2008	
Manufacturer	Camina & Schmid Feuerdesign und Technik GmbH & Co. KG	
Model	SH 8G / 8GB	
Nominal heat output [kW]	8	
Continuous burning appliance	—	
Type test standard	DIN EN 13229	
Year of testing	2007	
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Number of test laboratory	2	
Number of test report	RRF-29 06 1558	

Flue gas values

Wood
7.5
240
12

Further important characteristics of the appliance			
Suitability for installation to a shared flue ¹⁾			
Connectivity to the central heating system	-		
General technical approval for room sealed operation	-		

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood		
Norm : Inset appliance with flat-layer firing	Evaluation	
D - 1.BImSchV	Stufe 2	
A - Austrian regulation referred to Art 15a B-VG	2015	
CH - Swiss clean air act	×	
F - Crédit d'impôt à la transition énergétique	7☆	

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliance with flat-layer firing	Evaluation
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024
CH - Swiss clean air act	