Appliances properties: Buderus, Bosch Thermotechnik GmbH - Logastyle Figura

Master data	
Date of entry	Jul 8, 2016
Manufacturer	Buderus, Bosch Thermotechnik GmbH
Model	Logastyle Figura
Nominal heat output [kW]	5.9
Continuous burning appliance	-
Type test standard	DIN EN 13240
Year of testing	2016
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF - 40 16 4268

Flue gas values

	Wood
Flue gas mass flow [g/s]	5.1
Flue gas mass flow [g/s]	330
Necessary flue draught [Pa]	12

Further important characteristics of the appliance		
Suitability for installation to a shared flue ¹⁾	_	
Connectivity to the central heating system	_	
General technical approval for room sealed operation	-	

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
) - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	×
- Crédit d'impôt à la transition énergétique	v

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation	
D - 1.BImSchV	!	
DK - Danish regulation for air pollution from wood burners	!	