Appliances properties: Austroflamm GmbH - Ke 75x39 K mit keramischen Aufsatzringen

Date of entryJan 3, 2012ManufacturerAustroflamm GmbHModelKe 75x39 K mit keramischen Aufs	
ManufacturerAustroflamm GmbHModelKe 75x39 K mit keramischen Aufst	
	atzringen
Nominal heat output [kW] 10.9	
Continuous burning appliance	
Type test standard DIN EN 13229	
Year of testing 2010	
Test laboratory RRF Rhein-Ruhr-Feuerstättenprüf	fstelle GmbH
Number of test laboratory 2	
Number of test reportRRF - 29 10 2474	

Flue gas values

	Wood
Flue gas mass flow [g/s]	8.23
Flue gas mass flow [g/s]	290
Necessary flue draught [Pa]	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	✓
Connectivity to the central heating system	-
General technical approval for room sealed operation	✓
Number of approval for room sealed operation	Z-43.12-273

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	× .
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	<u> </u>

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	