Appliances properties: Willach KG - Jupiter II X

Master data		
Date of entry Manufacturer	Oct 14, 2014 Willach KG	
Model	Jupiter II X	Destron CE
Nominal heat output [kW]	0	
Continuous burning appliance	-	
Thermal output	228526 kJ	
Type test standard	DIN EN 15250	
Year of testing	2011	
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	100000
Number of test laboratory	2	Contraction of the second
Number of test report	RRF - 50 11 2650, Bauartzulassung Z-43.12-150	

Flue gas values	
	Wood
Flue gas mass flow [g/s]	14.9
Necessary flue draught [Pa]	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	-
General technical approval for room sealed operation	—

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood		
Norm : Slow heat release appliances	Evaluation	
D - 1.BImSchV	Stufe 2	
A - Austrian regulation referred to Art 15a B-VG	×	
CH - Swiss clean air act	×	
F - Crédit d'impôt à la transition énergétique	7☆	

Evaluation of emission data and efficiency Lignite briquettes

Norm : Slow heat release appliances	Evaluation
D - 1.BImSchV	!