Appliances properties: Camina & Schmid Feuerdesign und Technik GmbH & Co. KG - SD 9 E

Master data		
Date of entry Manufacturer	Aug 22, 2017 Camina & Schmid Feuerdesign und Technik GmbH & Co. KG	
Model	SD 9 E	
Nominal heat output [kW]	9	
Continuous burning appliance	—	
Type test standard	DIN EN 13229	
Year of testing	2016	
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	Printshi S
Number of test laboratory	2	
Number of test report	RRF - ITT 16 4508-1	

Flue gas values

Wood	Coal
9.3	9.3
279	227
12	12
	9.3 279

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	-
General technical approval for room sealed operation	—

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm : Inset appliances (with closed firedoor)	Evaluation	
D - 1.BImSchV	Stufe 2	
A - Austrian regulation referred to Art 15a B-VG	!	
CH - Swiss clean air act	•	
DK - Danish regulation for air pollution from wood burners	!	
F - Crédit d'impôt à la transition énergétique	5☆	

Evaluation of emission data and efficiency Lignite briquettes

Evaluation
Stufe 2
!
!