Appliances properties: skantherm GmbH & Co. KG - aerø

Master data	
Date of entry	Mar 6, 2012
Date of entry	
Manufacturer	skantherm GmbH & Co. KG
Model	aerø
Nominal heat output [kW]	9
Continuous burning appliance	—
Type test standard	DIN 18891
Year of testing	1994
Test laboratory	Deutsche Kohle Marketing GmbH
Number of test laboratory	22
Number of test report	91 92 18 Z

Flue gas values

	Wood
Flue gas mass flow [g/s]	23
Flue gas mass flow [g/s]	320
Necessary flue draught [Pa]	10

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	-
General technical approval for room sealed operation	_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2020
F - Crédit d'impôt à la transition énergétique	0
Evaluation of emission data and efficiency Lignite briquettes	
Evaluation of emission data and efficiency Lignite briquettes Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
Norm DIN EN 13240 (Intermittent burning): Roomheater	Evaluation