

Appliances properties: Palazzetti Lelio S. p. A. - ECOMONOBLOCCO S66 FRONTALE

Master data		
Date of entry	Mar 8, 2013	
Manufacturer	Palazzetti Lelio S. p. A.	
Model	ECOMONOBLOCCO S66 FRONTALE	
Nominal heat output [kW]	13.6	
Continuous burning appliance	_	
Type test standard	DIN EN 13229	
Year of testing	2008	
Test laboratory	KIWA GASTEC ITALIA S.P.A.	
Number of test laboratory	6	
Number of test report	400300	

Flue gas values

	Wood	
Flue gas mass flow [g/s]	12.3	
Flue gas mass flow [g/s]	263	
Necessary flue draught [Pa]	11	

Further important characteristics of the appliance		
Suitability for installation to a shared flue ¹⁾	_	
Suitability for installation to a shared flue?	_	
Connectivity to the central heating system	-	
General technical approval for room sealed operation	-	

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Inset appliance with flat-layer firing	Evaluation
D - 1.BlmSchV	×
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	7*

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliance with flat-layer firing	Evaluation
D - 1.BImSchV	

According to the transitional rule §26 the appliance can be used until 31.12.2024