Appliances properties: Spartherm Feuerungstechnik GmbH - Varia 2Rh 80 16,0kW – A E

Master data		
Date of entry	Apr 5, 2013	
Manufacturer	Spartherm Feuerungstechnik GmbH	
Model	Varia 2Rh 80 16,0kW – A E	
Nominal heat output [kW]	16	
Declared nominal space heating output [kW]	16	
Continuous burning appliance	-	
Type test standard	DIN EN 13229	
Year of testing	2013	
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Number of test laboratory	2	
Number of test report	RRF - 29 13 3203	

Flue gas values

	Wood
Flue gas mass flow [g/s]	12.91
Flue gas mass flow [g/s]	305
Necessary flue draught [Pa]	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	_
Connectivity to the central heating system	_
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	× .
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	<u> </u>

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	