

Appliances properties: LEDA Werk GmbH & Co. KG - KARAT KE 710 HD

Mar 6, 2012
LEDA Werk GmbH & Co. KG
KARAT KE 710 HD
8
_
DIN EN 13229
2011
RWE Rheinbraun AG
4.1
FSPS-Wa 2001-EN

Flue gas values

	Wood
Flue gas mass flow [g/s]	8.5
Flue gas mass flow [g/s]	230
Necessary flue draught [Pa]	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	-
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	× .
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	<u> </u>

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	