## Appliances properties: Camina & Schmid Feuerdesign und Technik GmbH & Co. KG - Ronda/Ronda FD (6745, 6745h, 6751, 6751h, 6757, 6757h)

Master data	
Date of entry	Feb 21, 2008
Manufacturer	Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
Model	Ronda/Ronda FD (6745, 6745h, 6751, 6751h, 6757, 6757h)
Nominal heat output [kW]	9
Continuous burning appliance	—
Type test standard	DIN EN 13229
Year of testing	2007
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF-29 06 1075

Flue gas values

Wood
7.6
340
12

Further important characteristics of the appliance	
Suitability for installation to a shared flue <sup>1)</sup>	
Connectivity to the central heating system	_
General technical approval for room sealed operation	-

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Inset appliances (with closed firedoor)	Evaluation
ImSchV	Stufe 2
trian regulation referred to Art 15a B-VG	×
wiss clean air act	×
dit d'impôt à la transition énergétique	

## Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024
CH - Swiss clean air act	!