Appliances properties: Ganz Baukeramik AG - Rumba

Oct 26, 2012	
Ganz Baukeramik AG	the second
Rumba	Ĩ.
7	
7	
-	
DIN EN 13240	
2006	
RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
2	
RRF - 40 05 912	
	Ganz Baukeramik AG Rumba 7 7 DIN EN 13240 2006 RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH 2

Flue gas values

	Wood
Flue gas mass flow [g/s]	7
Flue gas mass flow [g/s]	311
Necessary flue draught [Pa]	10

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	_
General technical approval for room sealed operation	_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Grandfathering
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	_
F - Crédit d'impôt à la transition énergétique	×

Evaluation of emission data and efficiency Lignite briquettes Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing Evaluation D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2024 DK - Danish regulation for air pollution from wood burners Image: Comparison of the transitional rule §26 the appliance can be used until 31.12.2024