

# Appliances properties: Spartherm Feuerungstechnik GmbH - Varia 1V H2O XXL 15,0kW - A1 (ab 01.2014)

Master data		
Date of entry	Feb 18, 2015	
Manufacturer	Spartherm Feuerungstechnik GmbH	
Model	Varia 1V H2O XXL 15,0kW - A1 (ab 01.2014)	
Nominal heat output [kW]	15	
Declared nominal space heating output [kW]	4	
Nominal water heating output [kW]	11	
Water operating pressure [bar]	3	
Continuous burning appliance	-	
Type test standard	DIN EN 13229	
Year of testing	2013	
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Number of test laboratory	2	
Number of test report	RRF - 29 13 3363	

Flue gas values	
	Wood
Flue gas mass flow [g/s]	13.1
Flue gas mass flow [g/s]	225
Necessary flue draught [Pa]	12

# Suitability for installation to a shared flue<sup>1)</sup>

#### Connectivity to the central heating system

### General technical approval for room sealed operation

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Evaluation of emission data and efficiency Wood

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	<b>7☆</b>

Evaluation of emission data and efficiency Lignite briquettes		
Norm : Inset appliances (with closed firedoor)	Evaluation	
D - 1.BlmSchV	0	