

Appliances properties: Olsberg GmbH - Olsberg - Pago Compact - 23/369

Master data		
Date of entry Manufacturer	Jan 9, 2008 Olsberg GmbH - Olsberg	
Model Product code Nominal heat output [kW]	Pago Compact 23/369 8	
Continuous burning appliance		
Type test standard Year of testing	DIN 18891 2004 DDE Dhair, Duba Esuaratitta gariifatalla Orabii	F
Test laboratory Number of test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH 2	
Number of test report	RO-9104687	

Flue gas values

Wood
8
310
11

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	-
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 1 Grandfathering
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	_
F - Crédit d'impôt à la transition énergétique	A

##