Appliances properties: Austroflamm GmbH - Pi

Master data	
Date of entry	Jun 20, 2012
Manufacturer	Austroflamm GmbH
Model	Pi
Nominal heat output [kW]	6
Continuous burning appliance	_
Type test standard	DIN EN 13240
Year of testing	2005
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF-40061013

Flue gas values

5	
	Wood
Flue gas mass flow [g/s]	6.9
Flue gas mass flow [g/s]	287
Necessary flue draught [Pa]	10

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	-
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 1 Grandfathering
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	•
F - Crédit d'impôt à la transition énergétique	5☆

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing

D - 1.BImSchV

Evaluation

According to the transitional rule §26 the appliance can be used until 31.12.2024

I