Appliances properties: Piazzetta S. p. A. - IL 75/66 V

Master data		
Date of entry Manufacturer Model Nominal heat output [kW]	Aug 6, 2014 Piazzetta S. p. A. IL 75/66 V 9	
Continuous burning appliance	_	5
Type test standard	DIN EN 13229	
Year of testing	2014	
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Number of test laboratory	2	
Number of test report	RRF - 29 14 3409	

Wood Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 340 Necessary flue draught [Pa] 12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	-
Connectivity to the central heating system	-
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	× .
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	<u> </u>

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	