

Appliances properties: Spartherm Feuerungstechnik GmbH - Varia 2RRh 7kW (Bauart A1; 2010)

Master data		
Date of entry	Jul 18, 2012	
lanufacturer	Spartherm Feuerungstechnik GmbH	
lodel	Varia 2RRh 7kW (Bauart A1; 2010)	
lominal heat output [kW]	7	
Declared nominal space heating output [kW]	7	
Continuous burning appliance	-	
ype test standard	DIN EN 13229	
ear of testing	2011	1.1
est laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
lumber of test laboratory	2	
lumber of test report	RRF - 29 11 2707	

Flue gas values

	Wood
Flue gas mass flow [g/s]	7.6
Flue gas mass flow [g/s]	245
Necessary flue draught [Pa]	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	_
General technical approval for room sealed operation	_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood		
lorm : Inset appliances (with closed firedoor)	Evaluation	
D - 1.BImSchV	Stufe 2	
A - Austrian regulation referred to Art 15a B-VG	2015	
CH - Swiss clean air act	× .	
F - Crédit d'impôt à la transition énergétique	7\$	

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	ļ