Appliances properties: Justus GmbH - Seeland, drehbar - 4965 22

Aaster data		
ate of entry	Dec 16, 2015	-
anufacturer	Justus GmbH	G
odel	Seeland, drehbar	
roduct code	4965 22	
ominal heat output [kW]	5	
eclared nominal space heating output [kW]	5	
ontinuous burning appliance	-	100
/pe test standard	DIN EN 13240	
ear of testing	2014	
est laboratory	Strojirensky Zkusebni Ustav s.p.	
umber of test laboratory	19	
umber of test report	30-12341-T-1	

Flue gas values

	Wood	Coal
Flue gas mass flow [g/s]	5.8	6.5
Flue gas mass flow [g/s]	216	219
Necessary flue draught [Pa]	12	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	_
General technical approval for room sealed operation	—

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	× .

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	×