

ſ

Appliances properties: Spartherm Feuerungstechnik GmbH - Varia 2L-55h (ab 07.2018)

Master data	
Date of entry	Aug 1, 2018
Manufacturer	Spartherm Feuerungstechnik GmbH
Model	Varia 2L-55h (ab 07.2018)
Nominal heat output [kW]	7
Declared nominal space heating output [kW]	7
Continuous burning appliance	-
Type test standard	DIN EN 13229
Year of testing	2017
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF - 29 17 4789

Flue gas values

	Wood
Flue gas mass flow [g/s]	6.1
Flue gas mass flow [g/s]	325
Necessary flue draught [Pa]	12

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	-
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood	
Norm : Inset appliances (with closed firedoor)	Evaluation
0 - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	×
- Crédit d'impôt à la transition énergétique	74

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	!
DK - Danish regulation for air pollution from wood burners	•